


YC-934

木器塗佈機



DOUBLE ROLLER COATER

影片連結 ▶



特性：

1. 採用機械塗佈，亦可獲致完全塗佈效果、省時、省力。
2. 備有兩組UV塗佈輪，可同時使用或單獨使用。
3. UV塗佈輪換裝容易，僅需將UV塗佈輪之固定套拆下即可換裝、省時、省力。
4. UV塗料回收迅速方便。
5. 送料速度可配合塗佈速度調整。
6. 本機適於木器合板塑膠噴射出門、窗及其他四方形、長方形之壁板之塗佈。

FEATURES :

1. Adopted mechanic spreading which can be achieved the spreading effectness perfectly, time & labour saving.
2. There equipped two sets UV spreading roller and employed in dual or single by selected.
3. Easy for replacing the spreading roller which is just to disassembly the locking bushing of UV spreading roller and replaced , time & labour saving.
4. UV spreading material convenient & rapid for recollecting.
5. The feeding speed can be adjusted couple with the spreading speed.
6. This machine is suitable for veneer board, plastic injectioned & extruded door, wall panel tec., after ashing making spreading use.

規格SPECIFICATIONS :

型式 Model	塗佈速度 Spreading speed	有效塗佈寬度 Eff. Spreading Width	有效高度 Eff. Spreading height	塗佈輪尺寸 Spreading roller size	動力 Power	電壓 Voltage	機械尺寸 Machine size	裝箱尺寸 Measurement	淨重/毛重 N.W./G.W.
YC-934	5~25m/min	300mm	3~40m/m	φ 240× 410mm	5HP	220V/380V/440V 客戶指定 on request	2220× 1360× 1300mm	2370×1520× 1460mm	800kg/1200kg
YC-934	5~25m/min	600mm		φ 240× 710mm	5HP		2220× 1698× 1300mm	2370×1850× 1460mm	1200kg/1700kg
YC-934	5~25m/min	1000mm		φ 240× 1200mm	5HP		2220× 2190× 1300mm	2370×2330× 1460mm	1800kg/2400kg
YC-934	5~25m/min	1300mm		φ 240× 1410mm	5HP		2220× 2360× 1300mm	2370×2520× 1460mm	2200kg/2800kg